

1. The unique identification code of the product type:

Dry pressed ceramic tiles with water absorption $E_b > 10\%$

2. Usage and intended application:

Material intended for wall lining interior

3. Manufacturer:

Ceramika Tubądzin II spółka z ograniczoną odpowiedzialnością
ul. Armii Krajowej 20, 95-035 Ozorków,
Polska

www.tubadzin.pl

4. Authorised representative: ND – not applicable

5. System of assessment and verification of constancy of performance of the construction:

Assessment system 4

6. Harmonized standard: EN 14411:2012

7. Declared performance

Essential characteristics	Performance	Technical specification
Reaction to fire	A1	EN 14411:2012
Breaking strength [N]	≥ 600	
Release of dangerous substances, for: -cadmium [mg/dm ²] -lead [mg/dm ²]	< 0,01 < 0,01	
Binding strength / adhesion [N/mm ²]: - Cement adhesives - Dispersion adhesives - Reactive resin adhesives - masonry mortar	$\geq 1,0$ $\geq 1,0$ $\geq 2,0$ NPD*	
Durability for: - Interior applications - Exterior applications: freeze – thaw resistance (frost resistance)	Compliant NPD*	
Resistance to thermal shock	Compliant	

* no performance defined

8. Appropriate technical documentation or special technical documentation:

The performance of the above specified product is compliant with the set of declared performance. This declaration of performance has been issued under the sole responsibility of the above specified manufacturer.

Signature on behalf of the manufacturer by:

Paweł Oskard

Member of the Board of Directors

Karol Chmielewski

Vice President of the Board of Directors

Ozorków, 22.12.2022